

# ShutterTech

## Australia

*Keeping it Simple*

Our Roller Shutters are suited for both residential and light commercial applications. Specifically designed to suit the harsh Australian climate, each Roller Shutter is custom made to ensure the right fit. Our Roller Shutters have profile lines on both the concave and convex sides.

### Technical Specifications

|                             |                      |
|-----------------------------|----------------------|
| Maximum Curtain Width       | 3600mm               |
| Maximum Surface Area        | 8.0m <sup>2</sup>    |
| Curtain Weight              | 4.0kg/m <sup>2</sup> |
| Profile Slat Height         | 40mm                 |
| Profile Slat Thickness      | 9.0mm                |
| Gauge of Aluminium          | 0.32mm               |
| Guide Dimensions (Standard) | 53mm x 22mm          |
| Guide Dimensions (Extended) | 68mm x 22mm          |
| Aluminium Axle              | 60mm Octagonal       |



# Residential Roller Shutters

## 40mm Curved Double Lined



### Why we recommended this product

- ◆ Potential heating and cooling energy savings of up to 40%
- ◆ Light control – up to 100% of UV and Infra-red rays with perforations to allow light into a room
- ◆ Noise reduction up to 50%
- ◆ Weather protection against rain, high winds and flying debris
- ◆ Fire protection against radiant heat and airborne ashes (not fire rated)
- ◆ Privacy and visual deterrent against forced entry
- ◆ Manufactured in Australia – offering the highest standards in technical support

## Available Colour Options

| Profile Colours | Colour Sample  | Pelmet, Side Frames, Guides, Bottom Bar |
|-----------------|--|---|
| White           |   | White                                   |
| Grey            |   | Grey                                    |
| Cream           |   | Cream                                   |
| Sand            |   | Sand                                    |
| Beige           |   | N/A (Profile Only)                      |
| Black           |   | Black                                   |
| Woodland Grey   |   | Woodland Grey                           |
| Deep Ocean Blue |   | Deep Ocean Blue                         |
| Green           |   | Green (Colourbond Pelmet)               |
| Red             |   | Red (Colourbond Pelmet)                 |
| Monument        |  | Monument                                |

\*Powder Coating options are available, however an additional fee will apply



Slats are double walled cavity, curved profile with a Polyurethane foam for added strength and insulation.

**Note:** Colours displayed are a guide only. Refer to production samples for final colour selection

### Pelmet Sizes

| Pelmet Size | Max. Shutter Height | Max. No. Slats |
|-------------|---------------------|----------------|
| 165mm       | 1700mm              | 42             |
| 180mm       | 2200mm              | 55             |
| 205mm       | 3150mm              | 78             |

### Control Options

|           |                                |
|-----------|--------------------------------|
| Motorised | FAAC Tubular Motor             |
|           | TUBE Tubular Motor             |
|           | Somfy Tubular Motor            |
| Battery   | Oz Roll E-Port Controller with |
| Manual    | Salento, Strap or Pull Winder  |
| Solar     | E-Solar Pro Unit               |

**ShutterTech**

**Australia**

*Keeping it Simple*

38 Radnor Drive, Deer Park VIC 3023

Tel: 03 8592 9404 | Fax: 03 8592 7910

E: [info@shuttertech.com.au](mailto:info@shuttertech.com.au) | Web: [www.shuttertech.com.au](http://www.shuttertech.com.au)