

40mm All Extruded Aluminium Roller Shutters

Keeping it Simple

Our All Extruded Roller Shutters are suited for both residential or commercial applications. It is BAL 40 Rated (tested by CSIRO) and suitable in areas prone to fire hazards. This profile offers superior strength for increased security. Overall appearance is clean and stylish with a slight groove line towards the bottom of the slat. Limited colour range available as a standard offering.



Why we recommended this product

- Bushfire Attach Level (BAL) 40 Rated
- Increased strength and security
- Heavy Duty axle and fittings
- Minimal flex
- Optional powder coating
- Ideal for commercial applications
- Tested through CSIRO against radiant heat

Slats have a 1mm gauge for added strength and security and can be powder coated to your choice of colour

Technical Specifications

Maximum Curtain Width	4000 to 4600mm
Maximum Surface Area	12.0m ²
Curtain Weight	$8.0 kg/m^2$
Profile Slat Height	40mm
Profile Slat Thickness	9.0mm
Gauge of Aluminium	1 mm
Guide Dimensions (Standard)	53mm x 22mm
Guide Dimensions (Extended)	68mm x 22mm

Available Colour Options

Profile Colours	White • Cream • Grey • Sand • Black •
	Woodland Grey • Deep Ocean Blue •
	Monument • Natural Anodised
Surrounds	White • Cream • Grey • Sand • Black •
	Woodland Grey • Deep Ocean Blue •



Keeping it Simple

38 Radnor Drive, Deer Park VIC 3023 Tel: 03 8592 9404 | Fax: 03 8592 7910

E: info@shuttertech.com.au | Web: www.shuttertech.com.au